Ambient & Rear Lighting





EXPERTS FOR AUTOMOTIVE ICs

We have a broad expertise in analog mixedsignal integrated circuit design.

We deeply understand our customers application needs to create real system innovation.

We are a global player for automotive ASSPs and ASICs. We offer worldwide sales and application support.

elmos

Copyright © 2022 Elmos Semiconductor SE. Confidential.

CORPORATE KEY FACTS



elmos

6 Elmos ICs

on average in every new car

6 product segments

Motor Control, Lighting, Safety/Power/Custom ICs, Ranging, Optical, Sensor ICs

16 locations worldwide

incl. 7 R&D centers, HQ located in Dortmund, Germany

35+ years of experience

in analog mixed signal IC solutions

~1,150 employees

thereof 350+ product developers & engineers

WE ARE LOCATED ALL OVER THE WORLD



PRODUCT SEGMENTS

- RANGING
- OPTICAL
- SENSOR ICs
- MOTOR CONTROL
- LIGHTING
- SAFETY, POWER & CUSTOM ICs



PRODUCT SEGMENT » LIGHTING

elmos

DRIVING USER EMOTIONS THROUGH LIGHTING DELIVERING CUSTOMIZATION, COMFORT AND SAFETY

- #1 in ambient light control
 - 250+ million LIN RGB controller ICs in the field
 - Auto-addressing easing module integration
 - All color homogeneous light output across temperatures

#1 in dynamic rear light animations

- Highest flexibility for LED control in dynamic animations
- Brightest output and best-in-class thermal management
- Constant light intensity at high temperatures
- Interface scalability and diagnosis for functional safety

LIGHTING APPLICATIONS

elmos

AMBIENT LIGHTING

LIN RGB Drivers Multichannel RGB Drivers

REAR LIGHTING

Static LED Drivers Multichannel LED Drivers

- Static & dynamic ambient lighting
- Homogeneous light output over full automotive temperature range
- Flicker free dynamic effects

- Static & dynamic pixel control
- Advanced thermal management
- All architecture interface scalability

elmos

Light Drives Emotion

8

LIN RGB LED DRIVERS

Delivering enhanced cockpit ambience and user experience through interior lighting

Use cases

 Floor light, roof light, reading light, door panels, cup-holders, dashboard surfaces, ...

USPs

- > 15 slave nodes auto addressing
- Precise LED forward voltage measurement system for high intensity variation and color temperature compensation
- Flicker free performance

STATIC LED DRIVERS

Delivering high brightness solutions for driving exterior lighting using advanced thermal management

Use cases

 Rear light, break light, CHMSL, turn indicator light, reverse light, fog light, DRL, ...

USPs

- Advanced thermal management for heat distribution
- Broad product portfolio for basic to extended feature sets
- Compatibility in groups and subgroups of products

MULTI CHANNEL LED DRIVERS

Delivering dynamic animations through individual LED control for exterior lighting

Use cases

 Rear light, break light, dynamic turn indicator, fog light, DRL, reverse light, front light grille, ...

USPs

- Advanced thermal management for heat distribution
- Interfaces to address all types of rear light architectures
- Communication protocols to address different data rates
- Developed according to ISO26262 to support ASIL B

ELMOS NEXT GEN LED DRIVERS

RGBW LED Driver with LIN Interface

Enables trend-setting, future-proof product concepts, resulting into stable modular platform designs, thereby reducing integration, development and qualification costs

Use cases

lighting stripes, floor lights, door panels, ...

USPs

- 60mA output current per channel ideal for daytime ambient lighting
- Auto Addressing feature allowing >15 slave addresses in a single LIN communication bus
- 40% higher PWM frequency for reducing LED flickering and allowing eye-friendly light output
- 12-bit ADC resolution allowing high precision color compensation over temperature for homogeneity Copyright © 2022 Elmos Semiconductor SE. Confidential.

ELMOS NEXT GEN LED DRIVERS

12 channel RGB LED driver for dynamic applications for comfort and safety critical interior lighting

Use cases

 Side mirror warning, pedestrian/cyclist warning, lighting stripes, surfaces, floor lights, door panels, lighting integration with driver monitoring systems, ...

USPs

- Multiplex mode to address 6 RGBs
- Boost mode for 3 times max current
- 16-bit 1kHz PWM for flicker free performance
- High speed elmos Light bus protocol
- Scalable slave-node system for auto-addressing
- Developed according to ISO26262 to support ASIL B

IN DEVELOPMENT

ELMOS NEXT-GEN LIGHTING

3 channel Automotive LED Driver for driving rear lights and (dynamic) turn indicators

Use cases

 Rear lighting, turn indicators, DRL, logo light, fog light, reverse driving light, ...

USPs

- Advanced thermal management for heat distribution
- 3x 200mA each output current (total 600mA)
- Supports Single LED failure detection
- System cost reduction due to integration
- Offering a dynamic turn indicator function

IN DEVELOPMENT

ELMOS NEXT-GEN LIGHTING

16 channel LED Driver with UART over CAN-FD interface for automotive exterior light systems used for high speed LED light animations and direct BCM control

Use cases

 Rear lighting, turn indicators, DRL, front light grille, fog light, reverse driving light, ...

USPs

- Advanced thermal management for heat distribution
- Sleep mode to reduce internal power dissipation
- 2Mbps UART communication protocol
- 2x PWMIN inputs with priority for fallback functionality
- Integrated CAN FD PHY for long wire robustness
- Developed according to ISO26262 to support ASIL B

PPAP AVAILABLE

ELMOS NEXT-GEN LIGHTING

16 channel Standalone LED Driver with embedded animations for automotive exterior light systems targeting ECU less light animations

Use cases

 Rear lighting, turn indicators, DRL, front light grille, fog light, reverse driving light, ...

USPs

- Advanced thermal management for heat distribution
- Embedded memory to store predefined animation sequences
- 4x discrete inputs for triggering animation sequences
- Developed according to ISO26262 to support ASIL B

PPAP AVAILABLE

elmos

Innovation Matters

DISCLAIMER

This presentation contains forward-looking statements based on beliefs of Elmos' management. Such statements reflect the company's current views with respect to future events and are subject to risks and uncertainties. Many factors could cause the actual results to be materially different, including, among others, changes in general economic and business conditions, changes in currency exchange rates and interest rates, introduction of competing products, lack of acceptance of new products or services and changes in business strategy. Actual results may vary materially from those projected here. Elmos does not intend or assume any obligation to update these forward-looking statements.

elmos

Elmos Semiconductor SE

Heinrich-Hertz-Str. 1 | 44227 Dortmund | Germany | Telephone: + 49 231 75 49 0 | info@elmos.com | www.elmos.com